

# 1100 LITRE FLAT LID CONTAINER: THE BEST IN ITS CLASS



UNIQUE DESIGN EASY HANDLING IMPROVED SAFETY

# Improved handling

- Easy grip handles on all sides
- Optimum manoeuvrability
- Compatible with identification and weighing systems




# Increased safety

- Foot pedals on the front wheels lock the bin in position
- Increased stability
- Directional locks are ideal for use with towing equipment



### **Benefits**

- Accessories easily fitted
- Complies to EN840 standard
- Safe and easy handling



# 1100 Litre Flat Lid Container

#### **Material**

- Polymer components:
- ☐ Injection moulded from specially designed HDPE
- Resistant to decay, frost, heat and chemicals
- Special UV-stabilisers provide excellent ageing characteristics
- Corrosion resistant steel components
- Noise reduction:
- □ Wheel assemblies with solid rubber tyres
- Long service life:
- High quality materials
- Excellent manufacturing processes
- □ Withstands exposure to high mechanical stress levels
- Recycling:
- ☐ All container parts are recyclable

#### Design

- Easy handling through the use of ergonomic handles
- Versatile, with a comprehensive accessories range
- In accordance with the safety requirements of EN-840
- Easy grip handles on all sides
- Safe, easy handling, even with heavy loads
- Various wheel assembly configurations for different applications
- Improved water drainage as a result of rounded lids
- Water drainage plug as standard<sup>†</sup>
- Compatible with identification and weighing systems
- Reinforced base, front and rear panels for greater stability
- Fitted as standard with chip nest in accordance with RAL GZ 951/1
- Easy to clean due to smooth surfaces and rounded internal corners

#### **Accessories**

■ For accessories and special design variations such as lid apertures, locks and towing brackets, please refer to the separate accessories sheet for 4-wheeled containers

Quality

- Certified according to DIN EN 840 and RAL GZ 951/1
- Constant quality control through manufacturers laboratory as well as independent institutes

## **Dimensions - Weights - Standards**

Nominal volume:

1100 litres

■ Net weight:

approx. 65 kg


Max. load:

440 kg

Permitted total weight:

510 kg

Measurements to be used as a guide only -variations will occur















Note: Certification and Quality Marks depicted in this brochure are registered to SULO Umwelttechnik GmbH & Co. KG

#### Colours

- Standard colours: green, blue, yellow
- Special colours are available on request\*
- All additives are cadmium free and environmentally friendly







#### Imprints and markings

- Manufacturer, year of manufacture, material
- Nominal volume, max. permitted total weight
- EN 840, RAL markings
- Individual markings with imprints, hot-foil printing or adhesive labels available on request \*



SULO MGB Australia Pty Ltd 123 Wisemans Ferry Road Somersby NSW 2250

**Australia** 

Tel: +61 (0) 2 - 4348 8188 Fax: +61 (0) 2 - 4348 8128 Internet: www.sulo.com.au E-mail: info@sulo.com.au SULO – Queensland Office 11 Argon Street Sumner Park QLD 4074 **Australia** 

Tel: +61 (0) 7 - 3725 5000 Fax: +61 (0) 7 - 3725 5099 SULO – Victorian Office 1950 Hume Hwy Campbellfield VIC 3061

**Australia** 

Tel: +61 (0) 3 - 9357 7320 Fax: +61 (0) 3 - 9357 7340 SULO - New Zealand PO Box 58 962 Greenmount, Manukau City 2141

**New Zealand** 

Tel: +64 9 - 968 2180 Fax: +64 9 - 968 2188